DIGITUS CONNECT

DC IC812I-MC / DC IC814I-MC / DC 816I-MC / DC IC 818I-MC
DC IC812IA-MC / DC IC 814IA-MC

KVM Switch 2/4/6/8 -port

Abb. DC IC-818I-MC

Eigenschaften

- Steuerung mehrerer PC über eine Tastatur, eine Maus und einen Monitor
- Umschaltung per Taste, HotKey oder Mausklick
- Unterstützt Standard PS/2 Maus & IntelliMaus (max. 5 Tasten/Scroll Maus). Volle Unterstützung der MS Intellipoint 5.0 und Logitech Mouseware Treiber
- Max. Auflösung 1920 x 1440 Pixel
- Videobandbreite 200 MHz
- Unterstützt DDC, DDCB, DDC2B
- Autom. Tastatur- und Mausemulation
- Autoscan, Autoskip Funktion
- Unterstützt Windows 95/98/98SE/Me/NT4.0/2000/XP, VISTA, DOS, Linux, Novell Netware, FreeBSD
- HotKey Funktion aktivieren/deaktivieren
- Keine Treiber erforderlich

©2004 All rights reserved

Technische Daten

Art.-Nr.		DC IC-812I-MC	DC IC-814I-MC	DC IC-812IA-MC	DC IC-814IA-MC	DC IC-816I-MC	DC IC-818I-MC
EAN-Nr.		167143	167150	167204	167211	167167	167174
PC-Anschlüsse		2	4	2	4	6	8
Port Wahl		Tasten / Hot Key / Mausklick					
LEDs	On Line	2	4	2	4	6	8
	Selected	2	4	2	4	6	8
Emulation	Tastatur	PS/2					
	Maus						
Anschlüsse -Tastatur	Konsole	1x6 pin mini-DIN Buchse (PS/2)					
	CPU Port	2x6 pin mini-DIN Buchse (PS/2)	4x6 pin mini-DIN Buchse (PS/2)	2x6 pin mini-DIN Buchse (PS/2)	4x6 pin mini-DIN Buchse (PS/2)	6x6 pin mini-DIN Buchse (PS/2)	8x6 pin mini-DIN Buchse (PS/2)
Anschlüsse -Mouse	Konsole	1x6 pin mini-DIN Buchse (PS/2)					
	CPU Port	2x6 pin mini-DIN Buchse (PS/2)	4x6 pin mini-DIN Buchse (PS/2)	2x6 pin mini-DIN Buchse (PS/2)	4x6 pin mini-DIN Buchse (PS/2)	6x6 pin mini-DIN Buchse (PS/2)	8x6 pin mini-DIN Buchse (PS/2)
Anschlüsse -Monitor	Konsole	1x HD-15 Buchse (Std. VGA/SVGA)					
	CPU Port	2x HD-15 Stecker (Std. VGA/SVGA)	4x HD-15 Stecker (Std. VGA/SVGA)	2x HD-15 Stecker (Std. VGA/SVGA)	4x HD-15 Stecker (Std. VGA/SVGA)	6x HD-15 Stecker (Std. VGA/SVGA)	8x HD-15 Stecker (Std. VGA/SVGA)
Anschlüsse -Audio,Mic. (Jack)	Konsole			1 x Audio, Microphone			
	CPU Port			2 x Audio, Mic.	2 x Audio, Mic.		
19" Winkel						2 Stck. inklusive	
Auflösung		1920x1440 (Max.), DDC, DDC2, DDC2B, DDC2AB, 200MHz					
Steckernetzteil		DC 9V 300mA (Min.)					
Scan Intervall		5 sec ~ 30 sec					
Gehäuse		Metall					
Gewicht		420 g	640 g	475 g	1085 g	1180 g	1450 g
Abmessungen (LxBxH)		128x75x45 mm	200x75x45 mm	128x75x45 mm	269x104x45 mm	269x104x45 mm	342x104x45 mm

©2004 All rights reserved